



I FEATURE

EXCELLENT THD PERFORMANCE IN A SMALL FOOTPRINT.

I APPLICATIONS

FOR USE WITH ADSL CHIPSET

特性

它具有优良的 THD 性能及较小的焊接表面积

用途

应用于 ADSL 模块中

I PART NUMBERING SYSTEM (品名規定)

<u>DA</u> 1	<u>RM06</u> 2	-	<u>001</u> 3
DIP ADSL LINE TRANSFORMER	DIMENSIONS CORE DIM		PART NUMBER
直插式 ADSL 线性变压器	磁芯尺寸型 RM6		成品流水号

I SPECIFICATIONS

PART NO	Turns Ratio (±2%)	INDUCTANCE (6-2)(3-5)@10KHz	DCR(ΩMAX) (6-2)(3-5)@20°C	Longitudinal Balance(dB Min)
DARM06-001	(6-2):(3-5)=1:1	3.2mH±5%	2.2 Ω	45 dB
DARM06-002	(6-2):(3-5)=1:1	6.0 mH±5%	2.4 Ω	45 dB
DARM06-003	(6-2):(3-5)=1:1	3.8 mH±10%	3.2 Ω	45 dB
DARM06-004	(6-2):(3-5)=1:1	5.38mH±10%	2.5 Ω	45 dB

I SCHEMATICS

